

OptiSquare 2x2 Optics for street and area lighting for use with LED modules according to Zhaga Book 15

Light distribution: Extra wide

Material: PMMA (clear) Screw fixing: for screws M3 Maximum torque: 0.5 Nm

Suitable forPhilips Fortimo Fast Flex LED 2x6 DA HE and LED modules with 12.5 mm pitch according to Zhaga Book 15

- Typical application:

 Car parks and parking area lighting

 Perimeter of car parks and parking areas


 Industrial lighting such as high-bay warehouses, packaging and shipping halls, production halls

Height	6 mm
Width	50 mm
Length	50 mm
Type of fixing	Screw fixing: (0.5 Nm) screws M3
LED Type	Philips Fortimo Fast Flex LED 2x6 DA HE and LED-Module according to Zhaga Book 15
Pitch distance	12.5 mm
Material	РММА
Colour	clear
Lense surface	High gloss
Permissible application temperature	-40 °C up to + 80 °C

pkg. wt. part no. 8 g **35.104.**1004.85

The presented information are for reference only. All lighting parameters are typical values. The light distribution depends on the used type of LEDs, position tolerance, chip size and used





Light distribution: Extra wide measured with Philips Fortimo Fast Flex LED 2x6 DA HE

Efficiency: 97%