

CERTIFICATE

No. U6 121194 0001 Rev. 00

Holder of Certificate: **BJB GmbH & Co. KG**

Werler Straße 1
59755 Arnsberg
GERMANY

Certification Mark:



Product:


**Power supplies
(INTRACK ADAPTOR DRIVER)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:

64142225005301A

Date, 2023-05-31



(Taylor Yao)

CERTIFICATE

No. U6 121194 0001 Rev. 00

Model(s): 32.901.300X; 32.901.400X;
32.901.301X; 32.901.401X

Brand Name: BJB



Parameters:

Rated Input Voltage: 400VAC (three-phase), 230VAC (single-phase)

Rated Frequency: 50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class I; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant current type

ta: -20...+40°C

tc: 70°C

Compatible Track: See below table for details

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN IEC 62384:2020

Production Facility(ies): 101070

CERTIFICATE

No. U6 121194 0001 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)
32.901.300X	0.3	20-48	1050	59	50
			900		43
			800		38
			700		34
			600		29
			500		24
			400		19
			350		17
			Compatible Track: 783YX.000; 25-XX-Y; 26-XX-Y; 19-XX-Y; 677X-YY; 7501-XX-YY; 7511-XX-YY; 7512-XX-YY; XTS4XXX-Y; XTSF4XXX-Y; RCS350 3C LXXXX-YY; PRO-04XX-Y; PRO-R4XX-Y; 9000(A)-X/Y-ST; 9000-X/Y-ST15; 9000-X/Y-TR; 9000-X/Y-H; T3XXYY; T3XXFY; S280ZZZZ		
32.901.400X	0.3	20-48	1050	59	50
			900		43
			800		38
			700		34
			600		29
			500		24
			400		19
			350		17
			Compatible Track: XTSC6XXX-Y; XTSCF6XXX-Y; PRO-06XX-Y; PRO-R6XX-Y; 9000A-X/Y-ST; 9000-X/Y-ST15; 9000-X/Y-TR; 9000-X/Y-H; TC3XXYY; TC3XXFY		
32.901.301X	0.2	20-48	700	59	34
			650		31
			600		29
			550		26
			500		24
			450		22
			400		19
			350		17
			Compatible Track: 783YX.000; 25-XX-Y; 26-XX-Y; 19-XX-Y; 677X-YY; 7501-XX-YY; 7511-XX-YY; 7512-XX-YY; XTS4XXX-Y; XTSF4XXX-Y; RCS350 3C LXXXX-YY; PRO-04XX-Y; PRO-R4XX-Y; 9000(A)-X/Y-ST; 9000-X/Y-ST15; 9000-X/Y-TR; 9000-X/Y-H; T3XXYY; T3XXFY; S280ZZZZ		
32.901.401X	0.2	20-48	700	59	34
			650		31
			600		29
			550		26
			500		24
			450		22
			400		19
			350		17
			Compatible Track: XTSC6XXX-Y; XTSCF6XXX-Y; PRO-06XX-Y; PRO-R6XX-Y; 9000A-X/Y-ST; 9000-X/Y-ST15; 9000-X/Y-TR; 9000-X/Y-H; TC3XXYY; TC3XXFY		