

P2F (Push-to-Fix) Fixing element for LED modules

Push in fixing: for hole pattern \varnothing 4.2 mm

Material: CrNi with silicone ring







Provides consistent and constant contact pressure by elastic silicone ring

Contact pressure: min. 5 N

- Quick assembly process improves production efficiency and reduces production costs
- Eliminates potential damage from screw fixing due to low insertion forces
- CrNi and silicone materials ensure long life reliability
- Reliable heat dissipation due to a constant pressure
- Suitable for Zhaga standardised hole sizes of \varnothing 4.7 mm in LED modules to ensure future proofed designs
- Assembly without any additional tools
- Solutions for Automation upon request
- Removable connection

Example of application:



part no.		Total thickness	Packaging	Ring color code
28.901.U162.10		1.5 - 2.0 mm	5.000 pieces	transparent colorless
28.901.U163.10		2.0 - 2.4 mm	5.000 pieces	transparent yellow
28.901.U164.10		2.4 - 2.7 mm	5.000 pieces	gray
28.901.U165.10		2.7 - 3.2 mm	5.000 pieces	white
28.901.U166.10		3.2 - 3.6 mm	5.000 pieces	blue
28.901.U169.10		4.0 mm	5.000 pieces	transparent gray

Accessories:

Magnetic bit **28.901.U811.10**

Bitholder **28.901.U801.89**

