
OptiSpot R Cover Ø 47.56 mm

35.908 \cdot Cover and diffusor plate for reflectors **35.835** with Ø 50 mm





pkg.. wt. part no. 375 3 g **35.908.**1004.85

OptiSpot R Cover - Cover plate

For use with reflectors 35.835.1001 - 1004.56 mit Ø 50 mm

Snap in fixing onto top side of the reflector by means of snap in hooks


Material: PC, clear

The following product properties are achieved by combining a reflector with a cover plate:

- Visible reflector design
- Dust proof
- Insect protection
- Contact protection (reflector)

Please do not touch the reflector inside with bare fingers.





pkg.	wt.	part no.
375	Зg	35.908.1004.89

OptiSpot R Cover - Diffusor plate

For use with reflectors 35.835.1001 - 1004.56 mit Ø 50 mm

Snap in fixing onto top side of the reflector by means of snap in hooks

Material: clearPC, satined surface

The following product properties are achieved by combining a relector with a cover plate:

- Soft transition of the color fringes
- Possibly visually disruptive openings of the connector
- are covered
- Dust proof

1,4

- Insect protection
- Contact protection (reflector)

Please do not touch the reflector inside with bare fingers.





Reflector series 35.835





35.835.1001.56 Spot

35.835.1002.56 Medium

35.835.1003.56 Flood



35.835.1004.56 Wide Flood



35.835.

with cover plate



35.835. with diffusor plate

Effect on the beam angle and the efficiency of the reflector when combined with a cover plate or diffuser plate. (measured with COB Citizen CLU02J and connector **47.360**.1020.50). The values are for reference only.

Beam angle (FWH reflector	HM)	Efficiency reflector	Beam angle (FWHM) with cover plate 35.908. 1004.85	Efficiency with cover plate 35.908. 1004.85	Beam angle (FWHM) with diffusor plate 35.908. 1004.89	Efficiency with diffusor plate 35.908. 1004.89
35.835 .1001.56	15°	86%	16°	82%	17°	82%
35.835 .1002.56	25°		26°		27°	
35.835 .1003.56	39°		39°		39°	
35.835 .1004.56	61°		60°		60°	